

PCE data sheet

article#	9504124
article description	Schrems BV 63/5 2x32/5 2x16/5 4xSSD Ea
description long	Mobiler Vollgummiverteiler Modell SCHREMS IP54 255x400x300 mit 1x Tragegriff oben und 2x Stellfüße unten (stapelbar) 2m Kabel H07RN-F 5G16mm² schwarz mit Stecker 63A 5p 400V 1xCEE-Steckdose 63A5p 400V durchgeschliffen 2xCEE-Steckdose 32A 5p 400V abgesichert ü. 2xLS 32A 3p C 2xCEE-Steckdose 16A 5p 400V abgesichert ü. 2xLS 16A 3p C 4xSK-Steckdose 16A 250V IP54 abgesichert ü. 2xLS 16A 1p C 1xFI 63A/4/0.03A (TYP A63AT) über alle 16- und 32A Ausgänge Leitungsschutzschalter und FI Fabrikat Eaton ÖVE / VDE Verteiler betriebsfertig angeschlossen Hinweis: Anzahl Abgangsstromkreise (Betriebsbereitschaft) Max. Summenstrom aller Abgangsstromkreise limitiert durch Nennbetriebsstrom I_{na}!
GTIN (EAN)	9003399424397
country of origin	AT
customs number	85371098
net weight	19.000 kg
packaging quantity	1

ETIM 7.0	EC000379
CEE socket outlet 16 A	2x16A5p400V
CEE socket outlet 32 A	2x32A5p400V
CEE socket outlet 63 A	1x63A5p400V
Number of socket outlets with protective contact	4
Protection	Over current switch
Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)
Number of miniature circuit breakers	6
Material housing	Rubber
Power supply/connection possibility	Feeder cable with plug
Type of mains connection	CEE 63 A
Cable length	2 m
Handling	Portable
Degree of protection (IP)	IP54
Colour	Black
Height	255 mm
Width	400 mm
Depth	300 mm



www.manufacturer-safety.info