


Opis produktu

JRA/S 4.230.5.1

JRA/S4.230.5.1 Blind/Roller Shutter Act, Travel Det, 4-f, 230 V AC, Man Op, MDRC



Ogólne informacje

Typ produktu	JRA/S 4.230.5.1
Kod zamówieniowy	2CDG110125R0011
Numer EAN	4016779698443
Opis katalogowy	JRA/S4.230.5.1 Blind/Roller Shutter Act, Travel Det, 4-f, 230 V AC, Man Op, MDRC
Opis	For the control of independent 230 V AC drives via ABB i-bus® KNX. The devices are designed for positioning blinds, roller shutters, awnings and other shading products as well as for controlling doors, windows and ventilation flaps. Additional auxiliary voltage is not needed. The travel times of the drive are detected automatically via current detection. To protect the drives, the output contacts are electromechanically locked against each other. Push buttons are located at the front of the device to control the outputs e.g. during commissioning. The current status of the output is displayed via LEDs.

Installation

Instrukcje i podręczniki	2CDG941067P0005
--------------------------	-----------------

Dane techniczne

Arkusz danych, informacja	2CDC506040D0201
---------------------------	-----------------

techniczna	2CDC506062D0202
Rodzaj prądu	AC
Funkcje specjalne	Switching
Zakres napięć	230 V AC
Napięcie wyjściowe (U_{out})	230 V AC
Maksymalny prąd przełączania	6 A
Maksymalna moc przełączania	2400 W
Straty mocy	0.25 W
Liczba wyjść	4
Ilość diod LED	1
Kompatybilne systemy magistralowe	KNX (TP)
Grupa produktowa	KNX
Typ montażu	DIN-Rail
Ręczna obsługa	Tak
Kolor	light grey
Liczba baterii	0
Funkcja aplikacji	Blind / Shutter / Shading Control

Normy środowiskowe

Stopień ochrony	IP20
Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami
Dane RoHS	2CDG510123-0100
Deklaracja REACH	9AKK107492A1906
Szablon raportowania CMRT	9AKK108468A3363

Wymiary

Szerokość w liczbie modułów	4
Szerokość netto	72 mm
Wysokość netto	90 mm
Głębokość / długość netto	64.5 mm
Masa netto	0.252 kg
Głębokość zabudowy (t_2)	64.5 mm
Schemat wymiarów	2CDC072033F0015



Certyfikaty i deklaracje (Numer dokumentu)

Certyfikat CB	9AKK107991A3191
Deklaracja zgodności UE	2CDK506041D2701
Certyfikat KNX	9AKK105710A0057

Klasyfikacje	
ETIM 8	EC001330 - Shutting actuator for bus system
ETIM 9	EC001330 - Shutting actuator for bus system
Kategoria WEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8537 10 91
eClass	V11.0 : 27143128
Kod klasyfikacji	A

Accessories				
Identifier	Description	Type	Quantity	Unit Of Measure
GHQ6310084R0111	JSB/S1.1 Shutter Control Unit, MDRC	JSB/S 1.1	1	sztuka

Kategorie	
Produkty niskiego napięcia i systemy → Building and Home Automation Solutions → KNX → Shading Control → Blind Actuators 230 V AC	



360°