



Figure similar

SENTRON, uchwyt bezpiecznika cylindrycznego, 10x38 mm, 3-bieg., In: 32 A, Un AC: 690 V, sygnalizator LED, wersja kompaktowa

Wersja	
Nazwa markowa produktu	SENTRON
oznaczenie produktu	Uchwyt bezpiecznika cylindrycznego
wykonanie produktu	Sygnalizator LED, wersja kompaktowa
Ogólne dane techniczne	
liczba biegunów	3
wielkość wkładki bezpiecznikowej	10 x 38 mm
Napięcie zasilania	
napięcie robocze	
• przy AC wartość znamionowa	690 V
Stopień ochrony IP	IP20
Konstrukcja mechaniczna	
wysokość	90 mm
szerokość	45 mm
głębokość	58 mm
masa netto	212 g
Certyfikaty	
oznaczenie środków roboczych zgodnie z IEC 81346-2:2009	F
Zezwolenia Certyfikaty	
General Product Approval	

[Confirmation](#)



other

[Confirmation](#)

[Miscellaneous](#)

Więcej informacji
Informacje dotyczące opakowania
Informacje dotyczące opakowania
Information- and Downloadcenter (Catalogs, Brochures,...)
http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NW7034-1

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/pl/ps/3NW7034-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW7034-1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



Ostatnia zmiana:

24.09.2021 

