

## Interior Insulation box



### Interior Insulation box for insulation thicknesses 30 - 100 mm

- One-gang junction box for insulated interior walls
- including attachment adapter
- rear cable entries
- circumferential airtight sealing lip
- Can be combined with each other

|                                     |                  |
|-------------------------------------|------------------|
| <b>Article no:</b>                  | <b>1159-90</b>   |
| EAN:                                | 4013456544727    |
| Depth                               | 90 mm            |
| Adapter dimensions (LxWxD)          | 75 x 81 x 100 mm |
| for insulation thicknesses          | 30 - 100 mm      |
| Device screws                       | 2                |
| Screw spacing                       | 60 mm            |
| Cable entries of up to Ø 11.5 mm    | 4                |
| Support connectors for each package | 3                |
| Halogen-free                        | Yes              |
| Packaging inner/dispatch            | 5/50             |

One-gang junction box for electrical installations in internal insulation systems. For permanently secure and heat-bridge-free installation of switches, sockets and other devices in internally insulated exterior walls. For optimal room climate with proven protection from moisture damage. For use in many internal insulation systems.

- For installation in insulated interior walls
- Guarantees installation without heat bridges
- Moisture regulating and insulating
- Prevention of moisture induced structural damage
- Suitable for use in many insulation systems
- For insulation thicknesses 30 to 100 mm
- Installation on masonry without plaster

