


Opis produktu

AS8.3

AS8.3 Interconnector



Ogólne informacje

Typ produktu	AS8.3
Kod zamówieniowy	2TKA00003691
Numer EAN	6438199005133
Opis katalogowy	AS8.3 Interconnector
Opis	Interconnector AS8.3 is used when low-voltage or strong-current circuit box groups are installed under different cover plates. With interconnector AS8.3 the distance between box centers are either 85 mm or 100 mm depending on installation. Additionally, AS8.3 can be used as a inlet for 20 mm flexible conduit with AU80 -range boxes. Made of halogen free material (IEC/61249-2-21).

Normy środowiskowe

Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami
Dane RoHS	9AKK106713A4634
Deklaracja REACH	9AKK106713A4633
Szablon raportowania CMRT	9AKK108468A3363

Wymiary

Szerokość netto	0.034 m
Wysokość netto	0.018 m
Głębokość / długość netto	0.034 m
Masa netto	0.01 kg

Charakterystyka zamówienia

Jednostkowe opakowanie	bag 50 sztuka
Waga opakowania brutto (poziom 1)	0.557 kg

Certyfikaty i deklaracje (Numer dokumentu)

Deklaracja zgodności UE	9AKK10103A2338
-------------------------	----------------

Installation

Instrukcje i podręczniki	No document needed
--------------------------	--------------------

Najczęściej Pobierane

Arkusze danych, informacja techniczna	No document needed
--	--------------------

Klasyfikacje

ETIM 8	EC002328 - Accessories/spare parts for junction boxes/cases for mounting in the wall
ETIM 9	EC002328 - Accessories/spare parts for junction boxes/cases for mounting in the wall
Kategoria WEEE	Product Not in WEEE Scope
WEEE B2C / B2B	Business To Business
CN8	39259080

Kategorie

Produkty niskiego napięcia i systemy → Installation Materials → Flush Mounted Boxes → Accessories for Plastic Flush Mounted Boxes → Other Accessories

