

PCE data sheet

article#	9545020
article description	Mobilverteiler Vollgummi Baureihe ZIRL BV 125/5 2x63/5 2x32/5 2x16/5 4x16/ IP54
description long	solid rubber distribution box series ZIRL IP54 527x400x270(HxBxT) universal mit 2x carrying handle on top and 2x standing feet on the bottom (stackable) 2m cable H07RN-F 5G35mm2 black with plug 125A 5p 400V 1xCEE-socket 125A 5p 400V protected with pre-fuse of supply line 2xCEE-socket 63A 5p 400V IP67 fused with 2xMCB 63A 3p C 2xCEE-socket 32A 5p 400V fused with 2xMCB 32A 3p C 2xCEE-socket 16A 5p 400V fused with 2xMCB 16A 3p C 4xCEE-socket 16A 3p 230V fused with 4xMCB 16A 1p C 4xSchuko-socket 16A 250V IP54 fused with 4xLS 16A 1p C 2xRCD 63A/4/0.03A (TYPE A 63AT) over 2x CEE 63/5 1xRCD 63A/4/0.03A (TYP A 63AT) over 2x CEE 32/5 fused with Tytan D02 63A 3p 1xRCD 63A/4/0.03A (TYP A 63AT) over 2x CEE 16/5 1xRCD 63A/4/0.03A (TYP A 63AT) over all 230V-outlets MCB and RCD made by SIEMENS distribution box is ready wired for using Note: Number of outgoing circuits (ready for operation)
GTIN (EAN)	9003399661839
country of origin	AT
customs number	85371098
net weight	43.600 kg

ETIM 7.0	EC000379
CEE socket outlet 16 A	Other
CEE socket outlet 32 A	2x32A5p400V
CEE socket outlet 63 A	2x63A5p400V
CEE socket outlet 125 A	1x125A5p400V
Number of socket outlets with protective contact	4
Protection	Over current switch/D0-system
Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)
Number of miniature circuit breakers	14
Material housing	Rubber
Power supply/connection possibility	Built-up plug
Type of mains connection	CEE 125 A
Cable length	2 m
Handling	Portable
Degree of protection (IP)	IP54
Colour	Black
Height	527 mm
Width	400 mm
Depth	270 mm



www.manufacturer-safety.info