

55507000	DATA SHEET	
Valid from: 03.07.2018	SILVYN® FPAC	

SILVYN® FPAC is a one-part conduit coupler made of polyamide. The coupler is needed for the extension from flexible coarse and fine pitch conduits and can be removed by using a screwdriver.



Material: PA 66

Features:
Fast assembly
Anti-vibration
Suitable for fine and coarse conduits
High mechanical strength
High pull off and pull through strength

Temperature range: -50°C up to +135°C

Colour:
Grey
Black (UV-Resistant)

Norm Reference:    **UL FILE NUMBER E308201**

Note: Free of Halogen, Sulphur and Phosphorous

Protection class: IP 66

Dimension table:

Part No.	Part name	Nominal size	Inner Ø mm	Outer Ø mm	Length mm
Grey					
5550 7000	SILVYN FPAC 16 GY	16	11	29	59
5550 7001	SILVYN FPAC 20 GY	20	14,5	32	71
5550 7010	SILVYN FPAC 21 GY	21	14,5	32	71
5550 7011	SILVYN FPAC 25 GY	25	19,5	39	81
5550 7020	SILVYN FPAC 28 GY	28	19,5	44	81
5550 7030	SILVYN FPAC 34 GY	34	26,5	51	87
5550 7031	SILVYN FPAC 42 GY	42	32,5	63	101
5550 7032	SILVYN FPAC 54 GY	54	42	76	114
Black					
5550 7005	SILVYN FPAC 16 BK	16	11	29	59
5550 7006	SILVYN FPAC 20 BK	20	14,5	32	71
5550 7015	SILVYN FPAC 21 BK	21	14,5	32	71
5550 7016	SILVYN FPAC 25 BK	25	19,5	39	81
5550 7025	SILVYN FPAC 28 BK	28	19,5	44	81
5550 7035	SILVYN FPAC 34 BK	34	26,5	51	87
5550 7036	SILVYN FPAC 42 BK	42	32,5	63	101
5550 7037	SILVYN FPAC 54 BK	54	42	76	114

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55507000EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------