



zacisk przyłączeniowy przepust kabla z prawej strony 690 V AC, DC 1000 V, 125 A
IP20

Wersja	
Nazwa markowa produktu	SETRON
oznaczenie produktu	Systemy szyn zbiorczych
wykonanie produktu	Akcesoria
Napięcie zasilania	
napięcie robocze przy AC wartość znamionowa	690 V
Połączenia	
moment dokręcenia	
• minimalny	1 N·m
• maksymalny	3,5 N·m
rodzaj przekrojów poprzecznych możliwych do podłączenia przewodów dla przewodów Cu wielożyłowy	6-50 mm ²
Konstrukcja mechaniczna	
wysokość	27,1 mm
szerokość	20 mm
głębokość	16,5 mm
długość	30 mm
masa netto	23,2 g
Zezwolenia Certyfikaty	
General Product Approval	other



[Confirmation](#)



[Miscellaneous](#)



[Miscellaneous](#)

other	Environment
Confirmation	Environmental Con- firmations

Więcej informacji
Informacje dotyczące opakowania Informacje dotyczące opakowania Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3760-5 Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/pl/ps/5ST3760-5

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3760-5

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

Ostatnia zmiana:

15.08.2023 

