



plug, female, 2x2-pole, ET200SP, interface module, KP32F, PN-PN coupler, grid size 5.08 mm cage clamp technology, internally bridged, color-coded, scope of supply: 10 plugs

General information			
Product type designation	Connector, female, 2x2-pin		
Installation type/mounting			
Wall mounting/direct mounting	Yes; can be plugged into SIMATIC HMI device		
Supply voltage			
Type of supply voltage	DC		
Rated value (DC)	24 V		
Interfaces			
HMI-side interface			
• Number of pins HMI-side	2; Outgoing side jumpered internally, color-coded		
Device-side interface			
• Number of pins device-side	4; Female, spring-loaded terminals 0.75 mm²		
Standards, approvals, certificates			
CE mark	Yes		
RoHS conformity	Yes		
China RoHS compliance	Yes		
Ambient conditions			
Ambient temperature during storage/transportation			
• min.	-20 °C		
• max.	70 °C		
Mechanics/material			
Design of housing	plastic		
Dimensions			
Width	10 mm		
Height	22 mm		
Thickness	25 mm		
Scope of supply			
Delivery quantity in pieces	10		
Other			
Merchandise	No		
Manufacturer name	SIEMENS AG		
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany		
Note:	For ET 200S, interface module, KP32F, PN/PN coupler		
Usable in the following products			
• Product 1	6AV3688-3EH47-0AX0		
• Product 2	6AV7863*		
• Product 3	6AV7862-2*		
Classifications			
		Version	Classification

eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval	EMV
--------------------------	-----

[Manufacturer Declaration](#)


EG-Konf.



[KC](#)


RCM


RCM

last modified:

11/3/2021 