



protective film 4" widescreen for KTP400 Basic 1st generation, KTP400 Basic 2nd generation, KTP400 Comfort, here the film must be cut to size. alternative: 6AV6574-1AD04-4AA0, scope of supply: 10 protective films

General information	
Product type designation	Protective film 4" widescreen
Installation type/mounting	
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Standards, approvals, certificates	
CE mark	Yes
RoHS conformity	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C
• max.	80 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	80 °C
Relative humidity	
• Operation, max.	90 %
• Condensation permissible	No
Mechanics/material	
Material	
• Plastic	Yes; Nonreflecting
Dimensions	
Width	131.6 mm
Height	107.6 mm
Thickness	0.125 mm
Scope of supply	
Delivery quantity in pieces	10
Other	
printable with laser printer	Yes
Merchandise	No
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Target devices	For KTP400 Basic, KTP400 Basic 2nd, KTP400 Comfort, KTP400F Mobile
Usable in the following products	
• Product 1	6AV2124-2DC01-0AX0
• Product 2	6AV6647-0AK11-3AX0
• Product 3	6AV6647-0AA11-3AX0
• Product 4	6AV2123-2DB03-0AX0
• Product 5	6AV2125-2DB23-0AX0
Classifications	

	Version	Classification
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval	EMV
--------------------------	-----

[Manufacturer Declaration](#)



last modified:

8/1/2024