

backup battery for Mobile Panel, rechargeable, scope of supply: 1 backup battery, with 105 mm connection cable



General information	
Product type designation	Rechargeable back-up battery Mobile Panel
Installation type/mounting	
Mounting	pluggable
Wall mounting/direct mounting	Yes; in HMI devices, battery compartment
Supply voltage	
Design of the power supply	via basic unit
Type of supply voltage	DC
Rated value (DC)	3.7 V
Battery	
Design	
• Button cell	No
Accumulator	
Charge status display	No
Rechargeable	Yes
Capacity	1.85 A·h
Lithium-ion	Yes; 1/CP11/34/50 01 CGA
Special design	Yes; flat
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
CSA approval	No
UL approval	Yes
cULus	Yes
cURus	No
FM approval	No
RCM (formerly C-TICK)	No
KC approval	No
EAC (formerly Gost-R)	Yes
CCC	No
RoHS conformity	Yes
China RoHS compliance	Yes
Ambient conditions	
Suited for indoor use	Yes
Ambient temperature during operation	
• min.	-20 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-20 °C; shelf life at room temperature is 10 years with a capacity loss of 1 % per year

• max.	70 °C; shelf life at room temperature is 10 years with a capacity loss of 1 % per year			
Relative humidity				
• Operation, max.	90 %			
connection method				
Connector type		Connection plug		
Mechanics/material				
Enclosure material (front)		Yes		
• Plastic				
Dimensions				
Width		35 mm		
Height		50 mm		
Thickness		15 mm		
Width of the housing front		37 mm		
Height of housing front		77 mm		
Weights				
Weight (without packaging)		38 g		
Weight (with packaging)		56 g		
Scope of supply				
Delivery quantity in pieces		1; incl. 65 mm connecting cable		
Other				
Merchandise		No; 1S1P CGA103450A		
Manufacturer name		SIEMENS AG		
Manufacturer's address		Gleiwitzerstraße 555, 90475 Nuremberg, Germany		
contacting the manufacturer		Email: simatic_hmi_panel_helpdesk.i-ia@siemens.com		
Target devices		for Mobile Panel DP cabled, Mobile Panel PN cabled, Mobile Panel 277 IWLAN, Mobile Panel 277F IWLAN		
Note:		Dispose of battery (lithium) properly; hazardous product!		
Usable in the following products				
• Product 1		6AV6645-0AA01-0AX0		
• Product 2		6AV6645-0AB01-0AX0		
• Product 3		6AV6645-0AC01-0AX0		
• Product 4		6AV6645-0BA01-0AX0		
• Product 5		6AV6645-0BB01-0AX0		
• Product 6		6AV6645-0BC01-0AX0		
• Product 7		6AV6645-0DD01-0AX0		
• Product 8		6AV6645-0DE01-0AX0		
• Product 9		6AV6645-0DB01-0AX0		
• Product 10		6AV6645-0BE02-0AX0		
Classifications				
		Version	Classification	
	eClass	14	27-33-02-92	
	eClass	12	27-33-02-92	
	eClass	9.1	27-33-02-92	
	eClass	9	27-33-02-92	
	eClass	8	27-24-92-03	
	eClass	7.1	27-24-92-03	
	eClass	6	27-24-92-03	
	ETIM	9	EC002584	
	ETIM	8	EC002584	
	ETIM	7	EC002584	
	IDEA	4	3552	
	UNSPSC	15	32-15-17-03	
	Approvals / Certificates			
	General Product Approval		Dangerous goods	

[Manufacturer Declaration](#)



[Dangerous goods information](#)

last modified:

3/18/2025 