

Extension unit 12" PROFINET for mounting on all fully IP65-enclosed 16:9 HMI/IPC devices. For the flexible installation of operator controls, 6 mounting positions, 6 operator controls can be equipped; Connection via PROFINET (without equipment)



General information	
Product type designation	Extension Unit 12" PROFINET
Control elements	
With parameterizable keys	Yes
Connection type	
Connection type of the safety-related contacts (emergency stop)	8-pin connector
Installation type/mounting	
Mounting	For mounting on a 16:9 HMI / IPC PRO device (lower part)
Mounting type	Screwed joint
Rack mounting	No
Front mounting	No
Number of slots for command devices and signaling units	6
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	150 mA; without load
Power	
Active power input, typ.	3 W; Additionally 0.1 W per control element with LED
Interfaces	
Number of industrial Ethernet interfaces	2; For the construction of lines and rings without external switch
Number of PROFINET interfaces	2; Incl. switch
Protocols	
PROFINET	Yes
Redundancy mode	
Media redundancy	
— MRP	Yes
Test commissioning functions	
Key and signal lamp test	Yes; automatically when switching on
Degree and class of protection	
IP (all-round)	IP65
NEMA (front)	
Enclosure Type 4x at the front	Yes; All-round
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes

RCM (formerly C-TICK)	Yes		
KC approval	Yes		
Suitable for safety functions	Yes; e.g. installation of emergency stop		
Ambient conditions			
Ambient temperature during operation			
• min.	0 °C		
• max.	50 °C		
Ambient temperature during storage/transportation			
• min.	-20 °C		
• max.	60 °C		
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.	2 000 m		
Relative humidity			
• Operation, max.	90 %; no condensation		
Cables			
Cable length	30 m; Max. for emergency stop		
Mechanics/material			
Material			
• Aluminum	Yes		
Enclosure material (front)			
• Aluminum	Yes; Knockout covered with black film		
Dimensions			
Width	313 mm		
Height	99 mm		
Depth	100.65 mm		
Weights			
Weight (without packaging)	2.2 kg		
Scope of supply			
Delivery quantity in pieces	1		
Components included	Power supply connectors and 8-pole plug-in connectors for safety-related inputs		
Classifications			
		Version	Classification
	eClass	14	27-33-02-92
	eClass	12	27-33-02-92
	eClass	9.1	27-33-02-92
	eClass	9	27-33-02-92
	eClass	8	27-24-92-03
	eClass	7.1	27-24-92-03
	eClass	6	27-24-92-03
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03
Approvals / Certificates			
General Product Approval		EMV	

