



selector switch for Extension Units, 22 mm, round, plastic, latching, with integrated white LED, 3 switch positions 1-0-2, 2 NO contacts, without inscription, (incl. printed circuit board with contact module), scope of supply: 1 selector switch, 1 printed circuit board, including mounting accessories

General information	
Product type designation	Selector switch for Extension Unit
Control elements	
Version of actuating element	Rotary handle, 3 switch positions
Operating principle of the actuating element	Latching
Shape of actuating element	Round
Illuminant	Yes; Can be illuminated
• Type of light source	SMT LED
• Color of light source	Translucent white
Contact configuration	2 NO contacts
Installation type/mounting	
Mounting type	Threaded ring
Front mounting	Yes; Front plate attachment in an Extension Unit for 16:9 PRO devices
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption (rated value)	100 mA
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	No
Degree and class of protection	
IP (at the front)	IP65 (on front) to EN60529 and NEMA4
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; Only in combination with Extension Unit
cULus	Yes; Only in combination with Extension Unit
RCM (formerly C-TICK)	Yes; Only in combination with Extension Unit
Suitable for safety functions	No
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 500 m
Relative humidity	
• Operation, max.	90 %
• Condensation permissible	No

Mechanics/material				
Material				
• Plastic		Yes		
Material of the actuating element		plastic		
Material of the front ring		plastic		
Enclosure color (front)		gray		
Color of the front ring		Silver metallic		
Service life				
• Number of operating cycles, keys		300 000		
Dimensions				
Height of housing front		22.24 mm		
Mounting diameter		22.3 mm		
Weights				
Weight (without packaging)		50 g		
Weight (with packaging)		100 g		
Scope of supply				
Delivery quantity in pieces		1		
Other				
Target devices		Suitable for Extension Units of the 16:9 HMI/IPC PRO devices (refer to manual)		
Usable in the following products				
• Product 1		6AV7674-1LA31-0AA0		
• Product 2		6AV7674-1LA41-0AA0		
• Product 3		6AV7674-1LA51-0AA0		
• Product 4		6AV7674-1LA61-0AA0		
• Product 5		6AV7674-1LA32-0AA0		
• Product 6		6AV7674-1LA42-0AA0		
• Product 7		6AV7674-1LA52-0AA0		
• Product 8		6AV7674-1LA62-0AA0		
Classifications				
		Version	Classification	
		eClass	14	27-33-02-92
		eClass	12	27-33-02-92
		eClass	9.1	27-33-02-92
		eClass	9	27-33-02-92
		eClass	8	27-24-92-03
		eClass	7.1	27-24-92-03
		eClass	6	27-24-92-03
		ETIM	9	EC002584
		ETIM	8	EC002584
		ETIM	7	EC002584
		IDEA	4	3552
		UNSPSC	15	32-15-17-03
Approvals / Certificates				
General Product Approval	EMV			



last modified:

5/22/2024