



Figure similar

SIMATIC DP, INTERFACE DP/PA-LINK A. ET200M IM153-2 HF FOR EXPANDED TEMPERATURE RANGE FOR MAX. 12 S7-300 MODULES, WITH REDUNDANCY, TIME STAMPING FIT FOR ISOCHRON MODE NEW FEATURES: UP TO 12 MODULES CAN BE USED SLAVE INITIATIVE FOR DRIVE ES AND SWITCH ES EXTENDED DATA FOR HART SECON- DARY VARIABLES OPERATON W. 64-CHANNEL MODULES 32 SIGNALS / SLOT

General information	
Vendor identification (VendorID)	801Eh
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
permissible range (ripple included), lower limit (DC)	20.4 V
permissible range (ripple included), upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2,5 A
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption, max.	650 mA
Inrush current, typ.	3 A
I²t	0.1 A²·s

Output voltage	
Rated value (DC)	5 V
Output current	
for backplane bus (5 V DC), max.	1.5 A
Power loss	
Power loss, typ.	5.5 W
Address area	
Addressing volume	
• Inputs	244 byte
• Outputs	244 byte
Hardware configuration	
Number of modules per DP slave interface, max.	12
Time stamping	
Accuracy	1 ms; 1ms at up to 8 modules; 10ms at up to 12 modules
Number of message buffers	15
Messages per message buffer	20
Number of stampable digital inputs, max.	128; Max. 128 signals/station; max. 32 signals/slot
Time format	RFC 1119
Time resolution	0.466 ns
Time interval for transmitting the message buffer if a message is present	1 000 ms
Time stamp on signal change	rising / falling edge as signal entering or exiting
Interfaces	
Interface physics, RS 485	Yes
Interface physics, FOC	No
PROFIBUS DP	
• Node addresses	1 to 125 permitted
• automatic detection of transmission rate	Yes
• Output current, max.	70 mA
• Transmission rate, max.	12 Mbit/s
• Transmission procedure	RS 485
• SYNC capability	Yes
• FREEZE capability	Yes
• Direct data exchange (slave-to-slave communication)	Yes; Sender
• Connector type	9-pin sub D
1. Interface	
DP slave	
• GSD file	SI0480E.GSG

• automatic baud rate search	Yes
Protocols	
Bus protocol/transmission protocol	PROFIBUS DP to EN 50170
Isolation	
Isolation tested with	Isolation voltage 500 V
Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP20	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C
• max.	60 °C
Air pressure acc. to IEC 60068-2-13	
• Installation altitude above sea level, max.	3 000 m
Configuration	
Configuration software	
• STEP 7	Yes; STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	360 g
last modified:	10/28/2016