

B² conduit connectors



Conduit connector 90° for DIN EN conduit Ø 25 mm

- Toolless conduit connection to the B² one-gang junction boxes
- Accepts rigid and flexible conduits
- Damping of conduit vibrations during the compaction process
- Prevents the conduits penetrating the one-gang junction box and thus prevents conduits from being shortened later on
- Easy cable pull-in thanks to optimised 90° conduit elbow

Article no:	1262-25
EAN:	4013456588394
DIN EN conduit Ø	25 mm
Dispatch	100

The range of B² conduit connectors offers a secure and toolless conduit connection to the B² one-gang junction boxes without the need for special tools. The conduit connection created using a conduit connector is absolutely impermeable to concrete and safely dampens the vibrations of the conduits during the compaction process. As the conduit connection is made outside the B² one-gang junction boxes, no conduit protrudes into the interior of the box, thus eliminating the need to shorten the conduit on the inside. With the new 90° conduit connectors, sideways conduit connections can now also be easily implemented in narrow installation areas.

- Toolless conduit connection, no special tools required
- Precisely fitting "variable" conduit connection, absolutely sealed against concrete
- Damping of vibrations during the high-frequency or low-frequency compression process
- Conduit connection outside the one-gang junction box, no conduits protruding into the interior of the box
- Conduit connectors 90° for the lateral connection of conduits in narrow installation areas

