

Sound-insulation box 68 Flex



Sound-insulation box 68 Flex

- for sound insulation walls
- for accessories and electronic components
- Air-tight design with sealing membranes
- Elastic tunnel
- can be combined with sound insulation boxes 68

Article no:	9068-94
EAN:	4013456550407
For panel thickness	7 - 30 mm
Length	122 mm
Width	71 mm
Depth	75 mm
Cut hole Ø	68 mm
Screw spacing	60 mm
Device screws +/-	2
Tube entries up to M25	2
Cable entries 3 x 2.5 mm ² or 5 x 1.5 mm ²	2
Cable entries 3 x 1.5 mm ²	2
Air-tight	Yes
for sound insulation walls up to	68 dB
Halogen-free	Yes
Packaging inner/dispatch	10/100

Thanks to its solid box body, in connection with the sound absorbing surface on the box base the Sound insulation 68 Flex electronics box guarantees the wall's sound insulation function. Additional insulating strips minimise body sound transfer via the component opening. Fast installation is ideal for modernising or extending existing systems. The flexible tunnel makes it easy to install, and creates space for electronic components, cable reserves and terminals.

- Maintains the wall's sound insulation protection
- For Ø 68 mm installation openings
- Additional sideways terminal compartment for communications and network technology
- Toolless cable and conduit entry
- Can be combined with support connectors, air-tight and fully-insulated

