

Conduit one-gang junction box O-range ECON®



LUFTDICHT



O-range ECON® conduit one-gang junction box, air-tight, Depth 62 mm, halogen-free

- Air-tight design with sealing membranes
- fully-insulated through-wiring for combinations of one-gang junction boxes with support connectors
- toolless conduit entries

Article no:	9266-77
EAN:	4013456548749
For panel thickness	7 - 40 mm
Depth	62 mm
Cut hole Ø	68 mm
Device screws	2
Tube entries up to M20	2
Tube entries up to M25	2
Support connectors for each package	7
Halogen-free	Yes
Air-tight	Yes
Packaging inner/dispatch	25/250

Air-tight one-gang junction box with ECON® technology especially for installation with electrical installation conduit. The box is VDE-certified and suitable for energy-efficient electrical installation acc. to GEG. 4 entries are optimal for continuous conduit installation e. g. in prefabricated house construction or with data networks. Extremely easy fitting thanks to toolless conduit insertion with opening tab. The sealing membrane guarantees permanent air-tightness and at the same time retention of the conduit.

- Installation in Ø 68 mm cut hole
- Elastic sealing membrane for guaranteed air-tightness
- Toolless conduit entry
- Can be combined with support connectors, air-tight and fully-insulated

O-range ECON®

