

Junction box 120 mm air-tight



LUFTDICHT



Junction box Ø 120 mm O-range ECON®, air-tight, Depth 65 mm

- Air-tight design with sealing membranes
- for 2 electrical circuits through separator wall 9073-20
- receptacle for TS 35 standard rail
- with stable holding ring
- Cutting the installation opening with bi-metal cutter 1082-20 or VARIOCUT 1089-00
- including cover and screws

Article no:	9273-92
EAN:	4013456582071
For panel thickness	7 - 40 mm
Depth	65 mm
Cut hole Ø	120 mm
Tube entries up to M25	6
Cable entries 3 x 2.5 mm ² or 5 x 1.5 mm ²	6
Cable entries 5 x 2.5 mm ² or 7 x 1.5 mm ²	4
Cable entries 3 x 1.5 mm ²	6
Air-tight	Yes
Dispatch	10

Air-tight Ø 120 mm junction box with ECON® technology for an energy-efficient electrical installation in accordance with GEG. Extremely easy fitting thanks to toolless cable and conduit entry. The sealing membranes guarantee permanent air-tightness and at the same time retention of the cable or conduit. The large box volume provides plenty of installation space for various cable connections.

- Installation in Ø 120 mm cut hole
- Elastic sealing membrane for guaranteed air-tightness
- Toolless cable and conduit entry

