

PCE data sheet

article#	353408P
article description	Wallbox GLB 22kW, 5m cable Type2 + FI A
description long	Wallbox GLB - charging station for electric vehicles Connection: (230)400V AC, 50Hz, (single)3-phase Number of charging units: 1 fixed charging cable 4,5m with Type 2 connector Max. power per charging point: 22kW Charging current (min-max): 6A - 32A Nominal connection power: 22kW Protection: RCCB Type A, DC-fault protection (6mA) Access control: input for external key switch,... Material housing: Plastic/ black Lockable cover WxHxD: 205x422x124 mm Mounting method: Wall mounting Degree of protection: IP44 Impact strength: IK08 Ambient temperature: -25°C bis +40°C Standards: acc. EN 61851-1, IEC 61439-7 Adjustable charging current: 6A, 10A, 13A, 16A, 20A, 25A, 32A
GTIN (EAN)	7331185186863
country of origin	PL
customs number	85371098
net weight	5.960 kg
packaging quantity	0
minimum order quantity	1

ETIM 8.0	EC002883
Installation side connection model	3-phase
Number of charging units	1
Max. power per charging point	22 kW
Nominal connection power	22 kW
Width	205 mm
Height	422 mm
Depth	124 mm
Mounting method	Wall mounting
Number of socket outlets Type 2	1
Number of earth leakage circuit breakers type A	1
Material housing	Plastic
Degree of protection (IP)	IP44
Impact strength	IK08



<https://www.pcelectric.at/shop/en/?func=detail&artnr=353408P>



www.manufacturer-safety.info