

EKV1+0 95 VZC3FST (VZC3FST)

- Anti-rotation crimped cable lugs (type PK1)
- Earthing and short-circuiting devices can be configured online via the earthing and short-circuiting configurator



Type	EKV1+0 95 VZC3FST	
Part No.	VZC3FST	
Version	Single-pole	
Cable cross-section (phase side)	95 mm²	
Cable cross-section (earth side)	95 mm²	
Length of single-pole cable	5000 mm	
Cable cross-section	95 mm²	
Fully insulated	No	
Max. short-circuit current I _k 0.5 s	26.5 kA	
Max. short-circuit current I _k 1 s	18.7 kA	
Crimped cable lug	PK1	
Standard	EN/IEC 61138 (DIN VDE 0283-3) and EN/IEC 61230 (DIN VDE 0683-100)	
Temperature range	-25 °C ... +55 °C	
Material (cable)	E-Cu, extra finely stranded and highly flexible	
Material (sheath)	Thermoplastic polymer (flexible PVC compound YM2)	
Hole (cable lug)	Ø12.5 mm	
Weight	5,47 kg	
Customs tariff number (Comb. Nomenclature EU)	85359000	
GTIN	4013364163324	
PU	1 pc(s)	

Attention: Please state the relevant Variant No. when ordering.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.