Product Environmental Profile



Eaton Metering Board ZSD empty enclosure

Representative product	+ZSD-G59/31 (EP-503412) Product Category: Unequipped enclosures and cabinets
Description of the product	+ZSD-G59/31: Empty meter cabinet, protection class 2 with IP31 degree of protection.
Homogeneous Environmental Families Covered	The PEP concerns the following product offerings from Eaton ZSD-G59/31 Meter Cabinet as mentioned below: EP-503412 (reference), EP-503411, EP-503408, EP-503407, EP-503410, EP-503406, EP-503409, EP-503405.
Functional unit	"Protect people from direct contact with live active parts and ensure the grouping of control, command and protection devices in a single cabinet having the dimensions (HxWxD) as 1400mm x 1300mm x 225mm, with rated current (In) 63A, while protecting them against mechanical impacts IK08 and the penetration of solid objects and liquids (IP31), according to the appropriate use scenario, and for the reference service life of the product of 20 years."
Company information	Eaton elektrotechnika s.r.o, Suchdol nad Lužnicí 89, 378 06 Suchdol nad Lužnicí, Czechia Email: productstewardship-es@eaton.com

Constituent Materials			
Reference product mass	**5.18E+01** kg (With packaging)		
Category PEP Material	Material constituent	Mass (kg)	% Contribution
Metals	Steel	3.21E+01	62.0%
Other	Wooden pallet	7.33E+00	14.2%
Other	Cardboard	5.32E+00	10.3%
Plastics	Polystyrene	2.56E+00	4.9%
Plastics	Polyvinyl chloride	2.27E+00	4.4%
Other	Coating Powder	1.32E+00	2.5%
Plastics	Polypropylene	3.64E-01	0.7%
Plastics	Low Density Polyethylene (LDPE)	3.38E-02	0.1%
Plastics	Silicon Rubber	1.00E-01	0.2%
Plastics	Polyamide 66	8.42E-02	0.2%
Other	Others	2.88E-01	0.6%
Total		**5.18E+01**	**100%**

Substance Assessment
The representative product is compliant without exemption with the EU-RoHS Directive (2011/65/EU), and the product does not contain any substance listed as Substance-of-Very-High-Concern (SVHC) as Duty-to-Declare on the Candidate List of the EU-REACH Regulation (1907/2006/EC).

Additional Environmental Information	
Manufacturing	The reference product is assembled at an Eaton plant Czech Republic holding management system certifications according to ISO 14001 standards.
Distribution	Eaton is committed to minimizing weight and volume of product and packaging with focus to optimize transport efficiency.
Installation	The installation process does not require any energy consumption and there is no waste other than the obsolete product packaging generated during this step.
Use	The product does not require energy consumption and maintenance during operation.
End of life	The overall recyclability rate of the product is 62.6% if it is properly dismantled prior to shredding. The rate is calculated based on the End of life statistics in Table 7 of PCRv4.

Environmental Impacts	
The calculation of the environmental impacts is the result of the Product's Life Cycle Analysis in accordance with ISO 14040/44, covering the entire lifecycle, i.e., "Cradle-to-Grave" including the following life cycle phases: production, distribution, installation, use and end of life. System modelling was carried out using the commercial LCA software EIME v63.2-4 with database version CODDE-2025-04. Indicators Set: PEF EF 3.1 (Compliance: PEP ed.4, EN15804+A2) v2.0	
Manufacturing Phase	The product is assembled as well as packed at Eaton facility Eaton Suchdol nad Lužnicí 89, 378 06 Suchdol nad Lužnicí, Czechia. Energy model used: Czech Republic
Distribution Phase	Distribution of the product in its packaging from the Eaton's last logistics platform to the installation place in Europe is considered as per PCR rules.

Installation Phase	Product is installed in Europe. Installation of product and treatment of packaging waste are considered in this phase. There is no energy consumption for reference product. Energy model used: Europe
Use Phase	Reference lifetime: 20 Years Usage profile: No energy consumption by the product during its useful life. Also, product do not require any maintenance/replacement during useful life.
End of life Phase	Product is disposed in accordance with WEEE guidelines. Energy model used: Europe
Module-D	Module D is calculated according to PCR-ed4-EN-2021 09 06 based on the materials recycled and the modelled end-of-life scenario. It expresses the net benefits and loads beyond the boundaries of the system and are not to be included in the life cycle totals.

Environmental Impact Indicators: Mandatory

Mandatory environmental impact indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	C1-C4 - End of life	D - Benefits and loads beyond the system boundaries
Climate change - total (GWP)	kg CO_2 eq.	4.08E+02	3.34E+02	9.77E+00	2.67E+01	3.73E+01	-1.21E+02
Climate change - fossil fuels (GWP-f)	kg CO_2 eq.	4.05E+02	3.51E+02	9.77E+00	7.08E+00	3.71E+01	-1.25E+02
Climate change - biogenics (GWP-b)	kg CO_2 eq.	3.11E+00	-1.67E+01	3.82E-05	1.97E+01	1.68E-01	4.09E+00
Climate change - land use and land use transformation (GWP-lu)	kg CO_2 eq.	4.74E-05	1.89E-05	1.41E-05	2.04E-07	1.42E-05	0.00E+00
Ozone depletion (ODP)	kg eq. CFC-11	7.40E-05	7.18E-05	1.12E-07	1.30E-07	1.92E-06	-3.76E-05
Acidification (AP)	mole of H+ eq.	2.33E+00	2.09E+00	1.54E-02	2.70E-02	2.01E-01	-6.79E-01
Freshwater eutrophication (Ep-fw)	kg P eq.	1.41E-03	1.23E-03	3.58E-05	8.30E-05	6.08E-05	-4.36E-04
Marine aquatic eutrophication (Ep-m)	kg of N eq.	2.81E-01	2.43E-01	2.96E-03	9.12E-03	2.54E-02	-7.28E-02
Terrestrial eutrophication (Ep-t)	mole of N eq.	3.26E+00	2.84E+00	3.25E-02	7.55E-02	3.09E-01	-7.96E-01
Photochemical ozone formation (POCP)	kg of NMVOC eq.	1.03E+00	9.13E-01	1.04E-02	1.75E-02	8.73E-02	-3.00E-01
Depletion of abiotic resources - elements (ADP-e)	kg eq. Sb	3.17E-02	3.17E-02	3.12E-06	3.80E-07	5.87E-06	-1.78E-02
Depletion of abiotic resources - fossil fuels (ADP-f)	MJ	6.75E+03	5.94E+03	1.70E+02	8.46E+01	5.61E+02	-1.74E+03
Water scarcity (WDP)	m^3 of eq. deprivation worldwide	1.29E+02	1.22E+02	3.47E-01	5.95E-01	6.40E+00	-5.55E+01

*Note: The Impacts of phases B1-B7 are Zero (0), Hence not included in the table.

Inventory Flow Indicators: Mandatory

Inventory flow indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	C1-C4 - End of life	D - Benefits and loads beyond the system boundaries
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	MJ	2.07E+02	1.32E+02	5.25E-01	4.04E+01	3.45E+01	1.27E+00
Use of renewable primary energy resources used as raw materials	MJ	2.35E+02	2.35E+02	0.00E+00	0.00E+00	0.00E+00	-5.58E+01

Inventory flow indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	C1-C4 - End of life	D - Benefits and loads beyond the system boundaries
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	4.42E+02	3.67E+02	5.25E-01	4.04E+01	3.45E+01	-5.45E+01
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	MJ	6.56E+03	5.75E+03	1.70E+02	8.46E+01	5.61E+02	-1.74E+03
Use of non-renewable primary energy resources used as raw materials	MJ	1.93E+02	1.93E+02	0.00E+00	0.00E+00	0.00E+00	-3.86E+00
Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	6.75E+03	5.94E+03	1.70E+02	8.46E+01	5.61E+02	-1.74E+03
Use of secondary materials	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of non-renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Net use of fresh water	m^3	3.09E+00	2.86E+00	8.08E-03	4.02E-02	1.90E-01	-1.29E+00
Hazardous waste disposed of	kg	2.31E+03	2.30E+03	3.91E-02	1.19E+00	6.29E+00	-1.29E+03
Non-hazardous waste disposed of	kg	3.84E+02	3.49E+02	8.67E-01	1.86E+00	3.17E+01	-4.50E+01
Radioactive waste disposed of	kg	4.50E-02	4.22E-02	6.87E-04	4.29E-04	1.65E-03	-2.14E-02
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	4.34E+01	1.10E+01	0.00E+00	6.65E+00	2.57E+01	0.00E+00
Materials for energy recovery	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ by energy vector	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content of the product	kg of C.	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Biogenic carbon content of the associated packaging	kg of C.	5.18E+00	5.18E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

*Note: The Impacts of phases B1-B7 are Zero (0), Hence not included in the table.

Environmental Impact Indicators: Optional

Optional Environmental impact indicators	Units	Sum	A1-A3 - Manufacturing	A4 - Distribution	A5 - Installation	C1-C4 - End of life	D - Benefits and loads beyond the system boundaries
Emission of fine particles	incidence of diseases	6.17E-05	6.02E-05	1.36E-07	1.63E-07	1.28E-06	-3.06E-05
Ionizing radiation, human health	kBq U^{235} eq.	1.23E+02	1.13E+02	3.25E-01	1.42E+00	8.40E+00	-8.50E+00
Ecotoxicity, fresh water	CTUe	5.39E+03	4.58E+03	2.67E+02	1.05E+02	4.40E+02	-4.43E+02
Human toxicity, cancer effects	CTUh	3.35E-04	3.34E-04	1.80E-09	6.39E-07	5.41E-09	-1.86E-04
Human toxicity, non-cancer effects	CTUh	5.92E-06	5.52E-06	3.78E-08	2.73E-08	3.38E-07	-2.59E-06
Impacts related to land use/soil quality	-	4.43E+00	3.64E+00	4.00E-02	2.94E-02	7.26E-01	-3.25E-02
Total use of primary energy during the life cycle	MJ	7.20E+03	6.31E+03	1.71E+02	1.25E+02	5.95E+02	-1.80E+03

*Note: The Impacts of phases B1-B7 are Zero (0), Hence not included in the table.

To evaluate the environmental impact of other product covered by this PEP, multiply the impact figures by-

Factors for Manufacturing, Distribution, Installation, End-of-Life, and Module-D Phase:

Product Number	Description	Phases	GWP	GWP-f	GWP-b	GWP-lu	ODP	AP	Ep-fw	Ep-m	Ep-t	POCP	ADP-e	ADP-f	WDP
EP-503412 (reference)	+ZSD-G59/31	All phases	1.00												
EP-503411	+ZSD-G49/31	Manufacturing	0.74	0.76	1.05	1.16	0.36	0.57	0.59	0.59	0.60	0.61	0.33	1.50	0.61
		Distribution	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87
		Installation	0.86	0.86	0.87	0.95	0.82	0.83	0.92	0.86	0.82	0.83	0.75	0.83	0.89
		Use	1.00												
		End of Life	0.78	0.78	0.81	0.82	0.72	0.78	0.82	0.78	0.78	0.77	0.81	0.77	0.78
EP-503408	+ZSD-G57/31	Manufacturing	0.73	0.75	1.05	1.17	0.33	0.55	0.58	0.57	0.58	0.59	0.30	1.51	0.60
		Distribution	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87
		Installation	0.86	0.86	0.86	0.95	0.81	0.82	0.92	0.85	0.81	0.82	0.74	0.82	0.88
		Use	1.00												
		End of Life	0.78	0.78	0.80	0.81	0.72	0.77	0.81	0.77	0.78	0.77	0.80	0.77	0.78
EP-503407	+ZSD-G47/31	Manufacturing	0.58	0.60	0.98	1.17	0.05	0.33	0.37	0.37	0.37	0.39	0.00	1.62	0.40
		Distribution	0.76	0.76	0.76	0.76	0.76	0.76	0.76	0.76	0.76	0.76	0.76	0.76	0.76
		Installation	0.76	0.76	0.76	0.91	0.68	0.70	0.86	0.75	0.68	0.70	0.57	0.70	0.80
		Use	1.00												
		End of Life	0.69	0.69	0.66	0.68	0.76	0.69	0.68	0.70	0.70	0.70	0.67	0.71	0.68
EP-503410	+ZSD-G39/31	Manufacturing	0.50	0.52	0.89	1.12	-0.05	0.25	0.28	0.28	0.29	0.30	-0.10	1.57	0.31
		Distribution	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69
		Installation	0.48	0.49	0.48	0.73	0.35	0.40	0.66	0.49	0.37	0.40	0.17	0.39	0.56
		Use	1.00												
		End of Life	0.67	0.67	0.61	0.63	0.83	0.67	0.62	0.68	0.68	0.70	0.62	0.70	0.65
EP-503406	+ZSD-G37/31	Manufacturing	0.41	0.42	0.68	0.94	-0.07	0.18	0.20	0.21	0.22	0.23	-0.11	1.30	0.23
		Distribution	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
		Installation	0.29	0.33	0.27	0.42	0.22	0.26	0.45	0.32	0.24	0.26	0.09	0.25	0.37
		Use	1.00												
		End of Life	0.64	0.64	0.51	0.53	0.98	0.65	0.53	0.67	0.65	0.70	0.52	0.70	0.60
EP-503409	+ZSD-G29/31	Manufacturing	0.38	0.39	0.61	0.87	-0.05	0.18	0.20	0.21	0.21	0.23	-0.09	1.18	0.22
		Distribution	0.51	0.51	0.51	0.51	0.51	0.51	0.51	0.51	0.51	0.51	0.51	0.51	0.51
		Installation	0.26	0.31	0.24	0.34	0.22	0.26	0.39	0.30	0.24	0.25	0.13	0.25	0.34
		Use	1.00												
		End of Life	0.63	0.63	0.48	0.50	1.02	0.64	0.50	0.66	0.64	0.70	0.49	0.70	0.59
EP-503405	+ZSD-G27/31	Manufacturing	0.33	0.34	0.41	0.67	0.03	0.19	0.19	0.21	0.21	0.22	0.01	0.84	0.21
		Distribution	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40
		Installation	0.19	0.24	0.17	0.17	0.21	0.23	0.26	0.24	0.23	0.23	0.20	0.23	0.24
		Use	1.00												
		End of Life	0.60	0.60	0.41	0.42	1.10	0.62	0.42	0.63	0.61	0.69	0.42	0.69	0.55

Disclaimer
This Product Environmental Profile and its content is based on information available to us. It refers to the product at the date of issue. We make no express or implied representations or warranties with respect to the information contained herein.

Registration Number	EATO-00546-V01.01-EN	Drafting rules	PCR-ed4-EN-2021 09 06
Verifier accreditation Number	VH68	Supplemented by	PSR-0005-ed3.1-EN-2023 12 08
Date of issue	01-2026	Information and reference documents	www.pep-ecopassport.org
		Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14025: 2006			
Internal	X	External	
The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDemain)			
PEPs are compliant with XP C08-100-1:2016 and EN 50693:2019 The components of the present PEP may not be compared with components from any other program.			
Document complies with ISO 14025: 2006 « Environmental labels and declarations. Type III environmental declarations »			