

DELTA FLAT IP44, SM DARK GRAY/LIGHT GRAY SCHUKO
OUTLET 3FOLD HORIZONTAL, 10/16A 250V W. SCREWLESS
TERMINALS W. HINGED LID, 75X201MM



Model	
Design of the product	SCHUKO
Cover version	complete enclosure
Design of the special power supply unit	without special current supply
Design of the socket / according to VDE 0620 for severe conditions	No
Design of the phase tap	No
General technical data	
Marking / of socket outlet	without imprint
Mounting type	fixing with screw
Surface processing	others
Material	others
Protection class	
Protection class IP	IP44
Main circuit	
Operating frequency	
• minimum	50 Hz
• maximum	50 Hz

Operating voltage / Rated value	250 V
Operating current / Rated value	16 A

Appearance

Color	grey
-------	------

Product details

Product component	
• Ejection equipment	No
• Labeling field	No
• Increased touch protection	No
• Fault current protection	No
• miniature fuse	No
• Integrated / functional lighting	No
• Integrated / Light source	No
• Integrated / orientation lighting	No
• Hinged lid	Yes
Product feature	
• lockable	No
• halogen-free	Yes
• transparent	No

Product function

Product function	
• Socket selectable	No
• Overvoltage protection	No

Number

Number of units	3
Number of sockets / switchable	0

Connections

Arrangement of contacts / diagonal	No
Type of electrical connection	plug terminal

Mechanical Design

Height	75 mm
Width	198 mm
Depth	54 mm
Mounting type	surface mounted
Material / of the enclosure	plastic



ÖVE



VDE



[Typprüfbescheinigung/Werkszeugnis](#)

[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5UB4731>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5UB4731/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5UB4731

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

