Specifications



Photo is representative





Eaton CCP2RL-3-60CF

Eaton Bussmann series CCP UL98 fusible disconnect, Finger Safe, Lock-On provision, 600 Vac, 125 Vdc, 225A, UL98 fusible disconnect, Three-pole, 200 kA - CCP2RL-3-60CF

General specifications

PRODUCT NAME	Eaton Bussmann series CCP UL98 fusible disconnect
CATALOG NUMBER	CCP2RL-3-60CF
UPC	051712709958
PRODUCT LENGTH/DEPTH	2.9 in
PRODUCT HEIGHT	3.7 in
PRODUCT WIDTH	0.3 in
PRODUCT WEIGHT	3.7 lb
WARRANTY	Not Applicable
COMPLIANCES	CCC Marked
CERTIFICATIONS	Contact Manufacturer
PRODUCT TYPE	UL98 fusible disconnect

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	225 A
SHORT-CIRCUIT RATING	200 kAIC
VOLTAGE RATING	600 Vac, 125 Vdc

Physical details

NUMBER OF POLES	Three-pole

General information

SPECIAL FEATURES	Finger Safe, Lock-On provision
SUITABLE FOR FUSES	TCF6 to TCF60 TCF1RN to TCF60RN FCF1RN to FCF60RN

Resources

CATALOGS	CCP2RL-3-60CF~CCP2 3P 60A CF W/ ROTARY HandM LEFT Bussmann series complete full line catalog no. 1007
DECLARATIONS OF CONFORMITY	Eaton Bussmann EU Declaration of conformity 93-68-EEC2512
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CCP2RL-3-60CF

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.